

TECHNICAL DATA SHEET

Identification: VAPOR LOCK™ 20/21

What it does:	ULTRA-LOW PERMEABILITY ♦ SHRINKAGE REDUCING WATER/DAMP PROOFING ADMIXTURE
Application/uses:	Basements, Rooftops & Tunnels
Company Name:	Biorok
ABN:	86 158 108 091 – Under License from SPG
Address:	Suite 3, Level 1, 42-44 Waymouth Street, Adelaide 5000
Web:	www.biorok.com.au
Phone:	+61 08 8212 4052

DESCRIPTION

Vapor Lock™ 20/21 Waterproofing & Exterior Protection Concrete Admixture is a ready to use concrete admixture that has an inorganic chemical reaction with components of the cement and utilizes the water of convenience to eliminate the route of water ingress / egress. This reaction is a permanent and integral component of the finished concrete.

BASIC USES

Vapor Lock™ 20/21 waterproofs/densifies concrete to an industry leading level. Vapor Lock™ 20/21 should be added to concrete whenever superior water proofing, extended service life, chemical resistance and densification at an economical cost are desired.

MAJOR ADVANTAGES OF Vapor Lock™ 20/21

- Waterproofs concrete
- Increases concrete density and hardness
- Increased abrasion resistance
- Requires no Chemical Curing
- Stops ACR, ASR
- Effective in reducing:
 - Plastic & Drying Shrinkage Cracking
- Efflorescence
 - Freeze-thaw spalling
 - Delamination
 - Slab curl

TECHNICAL DATA SHEET

TECHNICAL AND PRODUCT DATA

Appearance:	Translucent
Odour:	None
Toxicity:	None
Flammability:	None
pH:	Neutral
Shelf Life:	Indefinite
Weight:	12kgs
Freeze Temp:	0 C°
Solvent: None.	Water base
Acid Resistance:	Excellent
Hazardous Vapours:	None
Colour:	
Capillary Break:	Integral C-S-H
Installation:	All cementitious materials that contain no Polymers
Number of Components:	1
Packaging:	1040 Litre IBC

APPLICATION INSTRUCTIONS

Cast-in Place Normal Weight Concrete-Vapor Lock™ 20/21 is dosed at 650 ml per 100 kg of cementitious materials and should be added with the head water or at the tail end of the load. This dose needs to be accurate to minus 0% plus 3%. Vapor Lock™ 20/21 must be administered by a concrete ready-mix provider or professional that is certified by SPG to work with this material and is aware of and follows all the protocols established by SPG.

SPECIAL HANDLING

Discard any frozen or separated, visually observable, product.

SAFETY

Please refer to SDS at www.biorok.com.au

PROJECT SPECIFIC WARRANTY

Project specific Warranties are available for water proofing and spalling elimination. These Warranty's must be pre-approved by manufacturer and contain certain limitations.

WARRANTY DISCLAIMER

The information herein is to assist customers in determining whether our products are suitable for their application. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to the contents and suitability. We warrant our products to meet our written specifications. Nothing herein shall constitute a warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.